




MODEL DL3FU

Submersible Pump



eDYNAMiQ

Eco, Dynamic and Integrated Quality



eDYNAMiQ

Eco, Dynamic and Integrated Quality

Key Features

- Heavy-duty, premium (IE3) efficiency, air-filled motor – operates cooler with higher efficiencies, resulting in reduced operating costs
- Oversized lifting bail – Stainless Steel
- Internal Cooling System (ICS) – Stainless Steel Cooling Jacket
 - Optional for 2hp - 5hp
- Multi-conductor cable – Single cable for power and control
- Watertight cable entry system – protects against moisture and capillary action; reduces maintenance costs
- Minimum 50,000 hours single and double row thrust bearings – long dependable operation, lowers maintenance costs
- High-efficiency impellers – handle stringy, fibrous material with the ability to pass large solids and prevent clogging; impellers are optimized for hydraulic coverage lowering operating costs
- Double mechanical seals - operate in a glycol solution (ICS motors) or an oil bath (non-ICS motors) providing longer service life and lower maintenance costs
- Stainless steel shaft – high tensile strength and corrosion resistance
- Replaceable wear components – maintain working clearances while reducing casing and volute costs
- Optional hardened impeller and suction cover – 55RC minimum

Applications

- Industrial
- Municipal
- Water
- Wastewater
- Lift Stations
- Packaged Pump Systems
- Storm Water and Flood Control

Specifications

- Discharge Size: 2" to 4"
- Range of HP: 2 to 5 HP
- Capacity: 13 to 525 GPM
- Head: 7 to 45 Ft.
- Max. solid diameter: 3 1/4"
- Max. liquid temperature: 104°F (40°C)

Detailed performance and technical data available
at pumpsebara.com/products/dl3fu/



Your Local EBARA Representative:



EBARA Pumps Americas Corporation
1651 Cedar Line Drive
Rock Hill, SC 29730
(803) 327-5005
pumpsebara.com